SPECIFICATIONS

General	AP515	AP585
Frequency Range	400-470MHz;136-174MHz	
Channel Capacity	32	128
Zone Capacity	2	8
Channels Per Zone		16
Channel Spacing	12.5kHz/20kHz/25kHz	
Operating Voltage	3.7V (rated) 7.4V (rated)	
Battery	4000mAh 3.7V	1500mAh 7.4V 2000mAh 7.4V (Optional)
Battery Life (5/5/90 Duty Cycle,High TX Power)	18h	12h(1500mAh) 16h(2000mAh)
Frequency Stability	±0.5ppm	
Antenna Impedance	50Ω	
Dimensions (H x W x D)	105*55*29.5mm	115*55*29.5mm
Veight(with antenna&battery)	200g ±5g	230g±5g
Display	\	1.44 inch LCD
BT (optional)	BT 5.0 BLE+EDR	
Receiver		
Sensitivity	0.18µV (12dB SINAD)	
Adjacent Channel Selectivity	TIA-603: 60dB@12.5kHz; 70dB@20/25kHz ETSI: 60dB@12.5kHz; 70dB@20/25kHz	
Intermodulation	TIA-603: 70dB@12.5/20/25kHz ETSI: 65dB@12.5/20/25kHz	
Spurious Response Rejection	TIA-603: 70dB@12.5/20/25kHz ETSI: 70dB@12.5/20/25kHz	
Blocking	TIA-603: 80dB; ETSI: 84dB	
Hum and Noise	40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz	
Rated Audio Power Output	0.5W	1W
Rated Audio Distortion	≤3%	
Audio Response	+1~-3dB	
Conducted Spurious Emission	<-57dBm	
Transmitter		
RF Power Output	VHF: 4-5W / 1W UHF: 3-4W / 1W	VHF: 5W / 1W UHF: 4W / 1W
FM Modulation	14	KOF3E@12.5kHz; KKOF3E@20kHz; SKOF3E@25kHz
Conducted/Radiated Emission	-36dBm < 1GHz; -30dBm > 1GHz	
Modulation Limiting	±2.5kHz@12.5kHz; ±4.0kHz@20kHz; ±5.0kHz@25kHz	
M Hum&Noise	40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz	
Adjacent Channel Power	60dB@12.5kHz; 70dB@20/25kHz	
Audio Response	+1 to -3dB	
Audio Distortion	≤3%	
10010 21301 1011		
Environmental		
Operating Temperature	-20°C to +60°C	
Storage Temperature	-40°C to +85°C	
ESD	IEC 61000-4-2 (Level 4) ±8kV (contact); ±15kV (air)	
Dust and Water Intrusion	IEC60529-IP54	IEC60529-IP54 (IP67 optional)
Humidity	MIL-STD-810 G	
Shock and Vibration	MIL-5TD-810 G	

ACCESSORIES

STANDARD ACCESSORIES:







































OPTIONAL ACCESSORIES:

Hytera Communications Europe 939 Yeovil Road, Slough, Berkshire, SL1 4NH info@hytera-europe.com | www.hytera-europe.com

www.facebook.com/

HyteraEurope







Hytera

0191 228 0466☑ info@apexradio.com www.apexradio.co.uk 2 102 Tantobie Road, Newcastle upon Tyne,

NE15 7DQ





Subscribe on YouTube

Hytera reserves the right to modify the product design and the specifications. In case of a printing error, Hytera does not accept any liability. All specifications are subject to change without notice.













WORK SMARTLY AND EFFECTIVELY

Compact and light, yet the AP5 series is coupled with a package of features to make it easy to get your work done. Voice broadcast confirms the operation of a programmable button or changing the channel of non-display radios. Also there are three kinds of optional signaling to deliver critical information by a simple press.



TRUSTWORTHY QUALITY

Hytera has the world's largest professional communication production line, and manufactures each walkie-talkie in accordance with Industry 4.0 standards. Our strict supplier management system certification ensures each component meets the quality control requirements to ensure the consistency of product quality.

KEY FEATURES

- 32/128 channels
- Auto scan
- Vote scan
- Priority channel hunt
- Squelch
- Clear audio
- H/L power switching
- HDC1200 signaling/2-Tone signaling/
- 5-Tone signaling (optional)
- CTCSS/CDCSS
- Talk around
- Timeout timer
- Voice broadcast
- BT (optional)
- Type-C charge plug

